HALOLUX CERAM ECO 205 W 230 V E27

HALOLUX CERAM ECO | Compact halogen lamps for use in narrow luminaires



- General illumination
- Mood lighting
- · Dining table lighting
- · Lighting for reading
- · Restaurants, hotels and similar prestigious applications

Product benefits

- · More compact dimensions than ordinary light bulbs
- $\boldsymbol{\cdot}$ The same pleasant quality of light as that of an incandescent lamp
- · No transformer required
- UV filter
- Contains no mercury, can be thrown away with normal household waste

Product features

- 100 % dimmable
- · Average life: 2,000 h
- · Available in higher wattages up to 205 W

Technical data

Electrical data


| Rated wattage | 205 W |
|------------------------------|-------|
| Nominal wattage | 205 W |
| Nominal voltage | 230 V |
| Rated power factor λ | 1.00 |

Light technical data

| Light color as per EN 12464-1 | Warm White |
|---|------------|
| Nominal luminous flux | 4200 lm |
| Rated luminous flux | 4200 lm |
| Color temperature | 3000 K |
| Color rendering index Ra | 100 |
| Starting time | 0.0 s |
| Warm-up time (60 %) | 0 s |
| Lumen main.fact.at end of nom.life time | 0.80 |

Dimensions & weight

| Length | 105.0 mm |
|---------------------------|----------|
| Overall length | 105.0 mm |
| Diameter | 32.0 mm |
| Light center length (LCL) | 75.0 mm |
| Outer bulb | T30 |



Product line drawing with letters

Colors & materials

| Lamp mercury content | 0.0 mg |
|----------------------|--------|
| Mercury-free | Yes |

Lifespan

| Nominal lamp life time | 2000 h |
|----------------------------|------------|
| Rated lamp life time | 2000 h |
| Number of switching cycles | 1000000 1) |

 $^{^{1)}}$ At 1 s on / 1 s off