


## ■ 4ArXS – For Architainment eXtreme Seal

The OSRAM 4ArXS HSD<sup>®</sup> 200W/60 is an ultra-longlife metal halide lamp with outer bulb and daylight-like 6000 K. The lamp is characterized by a high luminance and - with 2,000 hours - a high average service life. The "eXtreme Seal" technology enables higher pinch temperatures up to max. 450°C. The lamp is suitable for cold start only. The 4ArXS HSD<sup>®</sup> 200W/60 is perfect for use in effect and architectural effect lighting.

### ■ Technical data

Lamp / order reference		4ArXS HSD <sup>®</sup> 200W/60
Rated wattage	W	200
Rated voltage	V	70
Rated lamp current (~)	A	3.3
Ignition voltage (cold)	kV <sub>s</sub>	2.0
Luminous flux	lm	13,000
Color rendering index	CRI	> 80
Color temperature	K	6,000
Arc length	mm	5.0
Lamp length (overall) $l_1$	mm	max. 108
Bulb diameter $d$	mm	max. 23
LCL ( $a$ )	mm	55
Average service life	h	2,000
Base		GY 9,5



### ■ Lamp operation

Maximum permissible base temperature	°C	450 at Molybdenum foil / Pinch seal region (eXtreme Seal Technology)
Cooling		Convection or Fan
Burning position		any

The 4ArXS HSD<sup>®</sup> 200W/60 can be operated on electronic power supplies (ECG) and standard ballasts.

### ■ Selection of igniters and control gear

Igniters:	ERC 640041, Bag Turgi
Ballasts:	ERC 686823, Magnetek
ECG:	Schiederwerk EVG 2-20

Further information on operating and control device requirements is available with the OSRAM brochure "Guidelines for Control Gear and Igniters - Metal Halide Lamps Display/Optic", order reference 123T01E.

### ■ Safety instruction

Because of the high UV radiation emitted by 4ArXS HSD<sup>®</sup> lamps and the fact that they operate at high pressures, they may only be used in purpose-built enclosed housings. Suitable filters must be used to ensure that the UV radiation is reduced to an acceptable level.