

ALUline PRO III

Electrical, Technical and Ordering Data (Subject to change without notice)

Product Number	Description	Watts	Volts	Bulb	Base	Color Temp. (Kelvin)	Lumens	Beam Spread	Rated Avg. Life (Hrs.)	Candlepower
13396-6	ALU III IMM 50W G53 12V 8D	50	12	ALU Pro III	G53	3000K	950	8	3000	23,000
13397-4	ALU III IMM 50W G53 12V 24D	50	12	ALU Pro III	G53	3000K	950	24	3000	4000
13398-2	ALU III IMM 75W G53 12V 8D	75	12	ALU Pro III	G53	3000K	1575	8	3000	30,000
13399-0	ALU III IMM 75W G53 12V 24D	75	12	ALU Pro III	G53	3000K	1575	24	3000	5300
13400-7	ALU III IMM 75W G53 12V 45D	75	12	ALU Pro III	G53	3000K	1575	45	3000	1900

Shipping Data (Subject to change without notice)

Product Number	SKU UPC (87-11500)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High	SKU Dimensions (W x D x H) (In.)	Case Dimensions (W x D x H) (In.)	Pallet Dimensions (W x D x H) (In.)
13396-6	42652-9	13396-7	6	1.41	0.23	1104	138	8	3.38 x 3.38 x 4.44	10.67 x 7.32 x 5.16	50 x 36.6 x 41.28
13397-4	42655-0	13397-4	6	1.41	0.23	1104	138	8	3.38 x 3.38 x 4.44	10.67 x 7.32 x 5.16	50 x 36.6 x 41.28
13398-2	42698-7	13398-1	6	1.41	0.23	1104	138	8	3.38 x 3.38 x 4.44	10.67 x 7.32 x 5.16	50 x 36.6 x 41.28
13399-0	42700-7	13399-8	6	1.41	0.23	1104	138	8	3.38 x 3.38 x 4.44	10.67 x 7.32 x 5.16	50 x 36.6 x 41.28
13400-7	42702-1	13400-1	6	1.41	0.23	1104	138	8	3.38 x 3.38 x 4.44	10.67 x 7.32 x 5.16	50 x 36.6 x 41.28